

Engine Oil Flush

Nulon Engine Oil Flush (EOF) is formulated to dissolve and dislodge harmful sludge, dirt, varnish and other contaminants that accumulate within an engine's lubrication system between oil change intervals.

Although modern engines are cleaner from an environmental aspect, all the pollutants of engine combustion previously released into the atmosphere are now recirculated within the engine. Consequently, lubricating oils have a much more difficult task in cleaning and suspending all these additional contaminants.

When added to the crankcase oil prior to each oil and filter change, Nulon Engine Oil Flush greatly assists in ridding the engine of potentially damaging contaminants. Nulon Engine Oil Flush also helps to free sticky valves and hydraulic lifters. Thermal efficiency of the engine is also improved by ridding the engine of insulating sludge build-up. EOF provides a cleaner environment for fresh oil to operate, so the detergent dispersant and antioxidant additives in the new oil are not depleted as quickly.

Benefits:

- Extends engine life
- Helps free up sticky valve lifters
- Keeps oil strainer & pick-up clean
- Cleans & removes sludge, dirt & varnish
- Provides a cleaner environment for new oil
- Keeps new oil cleaner for longer

Features:

- Nulon Engine Oil Flush is extremely simple to use and improves the environment in which lubricating oil operates.
- EOF is suitable for use with all synthetic and mineral oils
- Suitable for petrol, diesel, LPG, old or new engines
- Safe to use in older engines
- Compatible with seals and all engine components

Directions for Use:

Prior to oil change, add to engine crankcase oil (up to 6 litres) and run the engine at idle for 10 -15 minutes. Stop the engine and drain/flush out the oil while warm. Install new oil and filter. Use EOF with each oil change to prevent sludge build up.

Caution:

To prevent possible engine damage, heavily sludged engines require professional removal and cleaning of oil sump, pick-up and rocker cover.

Application Rates:

Add one 300 ml bottle of Nulon EOF for every 6 litres or part thereof of engine oil.

Safety Directions:

Avoid contact with eyes or skin. DO NOT SWALLOW. Keep out of reach of children. Combustible. Keep away from heat or flame. Do not breathe vapour. Wash hands thoroughly after use. Not to be used as a food container.

First Aid:

For advice, contact a Poisons Information Centre (Phone e.g. Australia 131 126; New Zealand 0800 764 766) or a doctor (at once). If swallowed, do NOT induce vomiting. If in eyes, hold eyelids apart and flush the eye continuously with running water. If skin contact occurs, flush with running water.

Packaging:

300 ml bottle (6 per carton) **Part No.** EOF



Australia's Own

Nulon Products Australia Pty Ltd
17 Yulong Close Moorebank NSW 2170
Freecall: 1800 679 922

www.nulon.com.au
info@nulon.com.au