



GULF WESTERN
THE TOUGH AUSTRALIAN

PRODUCT DATA

Chain Bar Oil - Supertak

Protects Chains and Bars of High performance Chain Saws

Description

Gulf Western Chain Bar Oil protects bars and chains of high performance chain saws. Contains anti-wear additives and tackifiers to protect the bar and chain and minimise "throw-off" from the chain.

Summary of Benefits

- Excellent adhesion to the chain and bar.
- High level of protection ensures longer bar and chain life.
- Provides good antirust and storage protection.
- Good penetration of chain links.

Specifications

Chain Bar Oil meets the following international performance specifications:

- Minimum ISO Viscosity 150
- Maximum ISO Viscosity 220

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

Chain Bar Oil - Supertak

Protects Chains and Bars of High performance Chain Saws

Typical Characteristics

Grade:	Chain Bar Oil		ISO 150 –
Product Code:	30080		ISO 220
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.8830
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	150-220
@ 100°C	ASTM D445	cSt	15.1
Viscosity Index	ASTM D2270	-	~100
Pour Point	ASTM D97	°C	-12
Flash Point (COC)	ASTM D92	°C	>220

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.



GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au

Web: www.gulfwestern.com.au

ACN 087 558 398

