



GULF WESTERN
THE TOUGH AUSTRALIAN

PRODUCT DATA

Air Tool Oil

Air Tool Oil for Air Powered Tools

Description

Air Tool Oil is, designed to lubricate the internal parts of air operated tools, both piston and rotary type. It resists the formation of acids, sludge, varnish and rust that rob tools of speed and power. Especially engineered for the care of all piston-type and rotary air tools

Prevents deposits forming, and prevents rust during storage. Ensures adequate lubrication at start up.

Compatibility: Air Tool Oil is compatible with most pumps, valves, and seal materials. However, like all petroleum based oils it should not be used with rubber O-rings.

Contamination of Air Tool Oil with other oils, especially engine oils, must be avoided as it can form gels which impair air release, anti foaming and demulsibility of the fluid.

Summary of Benefits

- Low viscosity.
- Prevents formation of deposits.
- Removes rust and varnish.
- Prevents rust formation.
- Absorbs moisture, does not contain aggressive additives that attack seals.
- Made from highly refined base oils with low carbon forming characteristics to prevent the formation of sludge and deposits which can produce sluggish valve operation.

Specifications

Air Tool Oil meets the following international performance specifications:

- ISO Viscosity Grade 32

Air Tool Oil

Air Tool Oil for Air Powered Tools

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

Typical Characteristics

Grade:	Air Tool Oil	ISO VG 32	
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.865
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	32
@ 100°C	ASTM D445	cSt	4.3
Viscosity Index	ASTM D2270	-	>101
Pour Point	ASTM D97	°C	-27
Flash Point (COC)	ASTM D92	°C	>224

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.

Pack Sizes Available:

1lt - 30193, 250ml - 30192



GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au

Web: www.gulfwestern.com.au

ACN 087 558 398