

PRODUCT DATA

# XMP - 3 Motor Oil SH/CD 20W-50

Multigrade Engine Oil

#### Description

XMP Motor Oil is a 20W-50 motor oil ideally suited to vehicles (1998 or earlier), requiring a petrol engine oil meeting API SH or lower. For newer vehicles requiring API SL oils, use Hi Tech Premium.

#### **Summary of Benefits**

XMP Motor Oil offers:

- Suitable for pre 1999 vehicles.
- Low Phosphorus content will not harm catalytic converter exhaust systems.
- Can also be used for lubrication of lightly loaded diesel engines.

### **Specifications**

XMP Motor Oil meets the following international performance specifications:

- SAE Viscosity 20W-50
- MIL-L-46152B
- API SH, CD
- Ford ESE-M2C-153E
- GM 6048M

#### Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

#### Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

# XMP - 3 Motor Oil SH/CD 20W-50

Multigrade Engine Oil

## **Typical Characteristics**

Grade: Product Code:	XMP-3 Motor Oil 30022 Test Method	Units	20W-50
Density @ 15°C	ASTM D1298	kg/L	0.8865
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	163
@ 100°C	ASTM D445	cSt	18.5
Viscosity Index	ASTM D2270	-	125
Pour Point	ASTM D97	°C	-16
Flash Point (COC)	ASTM D92	°C	>205

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.







Premium Quality Lubricating Oils (Aust.) Pty LTD 92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au Web: www.gulfwestern.com.au