



GULF WESTERN

THE TOUGH AUSTRALIAN

PRODUCT DATA

Two Stroke – Air cooled

Air-cooled 2-Stroke Motor Oil

Description

Air Cooled Two Stroke Oil is a versatile high performance low ash engine oil for use in air-cooled 2-stroke motors. This product is formulated for use in oil injected and pre-mix systems.

Air Cooled Two Stroke Oil is recommended for 2-stroke lawn mowers, chain saws, brush cutters, motor bikes and other similar 2-stroke engine powered implements.

Note: This product is not suitable for use in outboard marine engines that call for a TCW 3. Two stroke pre-mix should not be stored for more than 3 months. The fuel should be stored in well-sealed steel cans or specially designed plastic containers.

Summary of Benefits

Air Cooled Two Stroke Oil offers:

- Suitable for API TA, TB, TC requirements.
- Low ash formulation controls piston, port and plug cleanliness.
- Contains a diluent to aid mixing with leaded and unleaded petrol.

Specifications

Air Cooled Two Stroke Oil meets the following international performance specifications:

- API TC
- JASCO FB

Two Stroke – Air cooled

Air-cooled 2-Stroke Motor Oil

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

Typical Characteristics

Grade:	Air Cooled Two Stroke Oil		
Product Code:	30083		
	Test Method	Units	
Density @ 15°C	ASTM D1298	kg/L	0.885
Kinematic Viscosity			
@ 40°C	ASTM D445	cSt	52.7
@ 100°C	ASTM D445	cSt	8.4
TBN	ASTM D2896	Mg KOH/g	1.1
Viscosity Index	ASTM D2270	-	155
Pour Point	ASTM D97	°C	-18
Flash Point (COC)	ASTM D92	°C	90
Sulphated	Ash ASTM D874	% mass	0.09
Colour			Green

Typical characteristics are only a guide to industry and are not necessarily manufacturing or marketing specifications and do not constitute any legal liability.



GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au

Web: www.gulfwestern.com.au

ACN 087 558 398