



GULF WESTERN

THE TOUGH AUSTRALIAN

PRODUCT DATA

Truck and Farm Grease

High Quality Heavy Duty, Tacky Lithium Complex Grease

Description

Gulf Western Truck and Farm Grease is a very high quality extreme duty application tacky lithium complex grease. It is suited to nearly all heavy duty greasing applications for agriculture, trucking, automotive, marine, industrial and earthmoving applications. It is formulated with a high base oil viscosity that offers excellent water washout and weld load properties. It is formulated from a combination of polybutene base stocks combined with lithium complex thickener, extreme pressure additives and effective rust, oxidation and corrosion inhibitors. Truck and Farm Grease resists water washout and "squeeze out" from surfaces requiring lubrication under load conditions. It has been specially formulated to include a shear stable tackiness agent which unlike other conventional lithium complex greases have this extra tenacity for stayput lubrication because of this added adhesive characteristic.

Recommendations

TRUCK and FARM GREASE is the ideal recommendation for use in extreme heavy-duty applications and where water washout and high thermal resistance are needed. These applications include all industrial, earthmoving, agricultural, automotive and marine equipment. It is also suited in very demanding applications including high temperatures, high and shock loads, dusty and wet environments. Also suitable for bearings, gears, couplings, turntables, pins, hammers, trailer bearings and most other applications as described above. Suitable temperature range is -20 – 185c however can work intermittently up to 210c.

Truck and Farm Grease

High Quality Heavy Duty, Tacky Lithium Complex Grease

Storage

All packages should be stored under cover to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the relevant Materials Safety Data Sheet, which can be obtained by contacting Gulf Western Phone: 02 9673 9600.

Typical Characteristics

	Test Method	
NLGI Grade	-	2
Soap Type	-	Lithium Complex
Colour		Red
Texture	-	Smooth, Tacky
Penetration at 25°C -		
Worked, 60 Strokes	ASTM D217	270
Worked, 100,000 Strokes, Change %	ASTM D217	275
Dropping Point, °C	ASTM D2265	260+
Roll Stability, Penetration Change %	ASTM D1831	+10
Leakage		1.5
Water Washout @ 80°C, %	ASTM D1264	<3.5
Oxidation Stability Pressure -		
Drop @ 100 Hour, kPa	ASTM D942	15
Timken, OK Load, Kg	ASTM D2509	30
4-Ball Weld, Kg/f	ASTM D2596	480
4-Ball Weld Scar, mm	ASTM D2266	0.42
Base Oil Visc @ 40°C,	ASTM D445	1600

The facts stated and the recommendations made herein are believed to be accurate. No guarantee of their accuracy is made however, and unless otherwise expressly provided in written contract, the products are sold without conditions or warranties, expressed or implied. Purchasers should determine the suitability of such products for their particular purposes. Effective January 2014.

Pack Sizes Available: 205lt - 60054, 20kg - 62054, 450gram - 60454



GULF WESTERN

THE TOUGH AUSTRALIAN

Premium Quality Lubricating Oils (Aust.) Pty LTD

92 – 96 Links Rd, St Marys, NSW 2760 PO Box: 515 Kingswood, NSW 2747

Phone: 02 9673 9600 Fax: 02 9673 9696

Email: sales@gulfwestern.com.au

Web: www.gulfwestern.com.au

ACN 087 558 398